

# DIESTONE DLS

# Satwipes

MULTI-PURPOSE SAFE SOLVENT

## SATWIPES CLEANING SYSTEM

### Presaturated solvent wipes

Approved in Aeronautical and Automotive Industries

Complies with BMS 15-5 F- AMS 3818 A- MC Donnell Douglas DMS 1820 E

- Nonwoven wiper in perforated rolls
- Reusable canister reduces wastes
- Saturated and dispensed through a center-pull canister
- Reduces solvent use and VOCs.
- A variety of solvents and custom blends available



Product	Description	Size	Quantity per bag	Quantity par case	Quantity per unit packaging
SatWipes	100 % rayon	150 x 230 (MM)	100	10	1000
SatWipes	100 % rayon	280 x 230 (GM)	75	8	600
SatWipes	100 % rayon	300 x 320 (JB)	350	1	350

## ACTIVE PRODUCT PROPERTIES – DIESTONE DLS

*(Approvals: please consult the specific technical data sheet DIESTONE DLS)*

DIESTONE DLS is a solvent composition with controlled volatility and weak odour. It is free from chlorinated hydrocarbons and used as a cleaning agent. The product provides maximum security: it does not contain the teratogenic or carcinogenic components toluene, ethylene or glycol ethers.

The flash point of 30°C (86°Fh) is stable in time and remains constant throughout the evaporation duration.

Very high solvent power which allows excellent cleaning and degreasing of metallic surfaces before painting.

Non corrosive on metals, including light alloys.

Efficient reactivation and cleaning of epoxy and polyurethane primers.

Pleasant odour.

**Socomor**  
Finishing Technologies

Support technique International / International Technical Support  
tel. +33 (0)2 97 43 76 90 fax +33 (0)2 97 54 50 26 E-mail Support@socomor.com

*Veillez consulter notre site Web pour connaître notre correspondant le plus proche  
Please consult our Web site to find our nearest correspondent*

[socomor@socomor.com](http://socomor@socomor.com)



## USES

### Painting and paint stripping shops, construction and assembly :

- Subsidiary stripper of dry paint films (elimination of polyvinyl primers and nitrocellulose lacquers).
- Removal of felt tip, inks, etc...
- Degreasing of metallic materials, epoxy/carbon composites and thermoplastic materials before painting.
- Cleaning of jointing, sealant and glue application equipment. Removal of excess quantities, marks and runs of jointing products, sealants and glues.
- Degreasing during maintenance operations.

## ACTIVE PRODUCT TECHNICAL CHARACTERISTICS

· Appearance .....	clear liquid
· Density at 21°C (68° Fh).....	0.89
· Flash point (ISO 2592) .....	30°C (86°F)
· Evaporation rate (NFT 30301).....	0.6
· Halogenated hydrocarbons .....	none

## PRECAUTIONS FOR USE AND STORAGE

Please consult the product safety data sheet.

**This technical data sheet replaces and cancels the previous one.**

The above details have been compiled to the best of our knowledge, they have, however, an indicative value only, and we therefore make no warranties and assume no liability in connection with any use of this information, particularly if a third party's rights are affected by the use of our products. The above information has been compiled based upon tests carried out by SOCOMOR ; all data is subject to change as Socomor deems appropriate. The data given is not intended to substitute for any testing you must conduct in order to determine the suitability of the product for your particular purposes. Please check your local legislation applicable to the use of this product. Should you need any further information please contact our services.

**Socomor**  
Finishing Technologies

Support technique International / International Technical Support  
tel. +33 (0)2 97 43 76 90 fax +33 (0)2 97 54 50 26 E-mail Support@socomor.com

*Veillez consulter notre site Web pour connaître notre correspondant le plus proche*  
*Please consult our Web site to find our nearest correspondent*  
[socomor@socomor.com](mailto:socomor@socomor.com)

